

Section 2. Physical data.

Material (at normal condition) Solid

Section 3. Fire and explosive.

Special fire fighting procedures Non flammable

Section 4. Reactivity data.

Stability Stable Hazardous decomposition products None



Material safety data sheet.

Section 5. Toxicological information.

Effect of overexposure

Acute - Basalt continuous filaments may cause mechanical irritation to the skin, eye and upper respiratory tract.

Chronic- there is no known health effects connected with long term use or contact with this product.

Precautions: Avoid contact with eyes. Avoid contact with skin. Avoid breathing dust. Do not swallow. Do not eat, drink or smoke in work area. Wash thoroughly after handling .

Section 6. Emergency and first aid procedures

Inhalation. Move person to fresh air. Seek medical attention if irritation persists. **Eye contact.** Flush eyes with running water for at least 15 minutes. Seek medical attention if irritation persists.

Skin contact. Wash with mild soap and running water. Use a washcloth to help remove fibers. To avoid more irritation, do not rub or scratch effected area. Seek medical attention if irritation persists.

Ingestion. Ingestion of this material is unlikely. If it does occur, watch the person for several days to make sure that intestinal blockage does not occur.

Section 7. Personal protection.

Respiratory protection. If use or application of this product generates dust, use a filter respirator.

Eye and face protection. Standard safety glasses with side shields. **Protective gloves.** Use gloves to protect against physical irritation or injury if required by handling conditions.

Section 8. Ecological information

Basalt fiber is generally considered to be an inert solid waste. No special precautions are needed in case of release or spill.

Section 9. Carcinogenicity status

These products are not listed as a carcinogens or suspected carcinogens by NTP, IARC or OSHA.